



AS07NS1HRA-G  
AS09NS1HRA-G  
AS12NS1HRA-G  
AS18NS1HRA-G  
AS24NS1HRA-G



Modello	UI	gray	AS07NS1HRA-G	AS09NS1HRA-G	AS12NS1HRA-G	AS18NS1HRA-G	AS24NS1HRA-G
Codice commerciale	UI		2501300GL	2501301GL	2501302GL	2501305GL	2501306GL
<b>Dati prestazionali</b>							
Potenza resa RAFF	nom (min-max)	kW	2 (1,1-2,9)	2,7 (0,9-3,2)	3,6 (1,4-3,9)	5,2 (1,5-5,6)	7 (2,0-7,3)
Potenza resa RISC	nom (min-max)	kW	2,2 (1,3-3,2)	2,8 (1,4-3,2)	3,7 (1,4-4,1)	5,8 (1,6-6)	7,5 (2,5-7,8)
Pdesign RAFF	capacità (35°)	kW	2	2,7	3,6	5,2	7
Pdesign RISC	capacità (-10°)	kW	2	2,4	3,2	5,2	5,6
Alimentazione		V-Ph-Hz	230-1-50	230-1-50	230-1-50	230-1-50	230-1-50
Volume aria trattato		m³/h	600	600	650	900	1200
<b>Unità interna</b>							
Potenza sonora		dB	52	52	54	57	62
Pressione sonora		dB(A)	38/33/26/22	38/33/26/22	39/34/27/23	44/40/35/32	47/43/37/35
Dimensioni	L x P x H	mm	855x204x280	855x204x280	855x204x280	997x235x322	1115x248x336
Peso netto		kg	10	10	10	13	16
<b>Dati idraulici</b>							
Tubazione liquido Ø		mm	6,35	6,35	6,35	6,35	9,52
Tubazione gas Ø		mm	9,52	9,52	9,52	12,7	15,88